DATASHEET

IE4 THREE PHASES MOTOR



GENERAL DATA

Motor Code:	**MS4-132M-8**
Power (kW):	**3**
Frame Size:	**132M**
Housing Material:	**Aluminium**
Net Weight (kg):	**61**
Insulation Class:	**F**
Protection Degree:	**IP55**
Service Duty:	**S1**
Efficiency Class:	**IE4**
Cooling Method:	**IC411**
Standard:	**IEC 60034**
Bearing Types:	**6308 ZZ**
Noise Level (dB):	**64**
Moment of Inertia (kg*m2):	**0.062355**
Ambient Temp.:	**-15C to +40C**
Altitude:	**1000m above sea level**

ELECTRICAL DATA

Power (kW):			**3**
Frequency (Hz):			**50HZ**
Speed (RPM):			**725.0**
Eff% (@400V)	**100%: 85.9**	**75%: 86**	**50%: 84.2**
Power Factor (Cos PHI):			**0.67**
Tst/Tn:			**2.5**
Tmax/Tn:			**3.1**
Tmin/Tn:			**2.1**
Ist/In:			**6.3**
Moment of Inertia (kg*m2):			**0.062355**


Current (A)		
220V	380V	660V
13.7	**7.92**	**4.56**

Current (A)		
230V	400V	690V
13.1	**7.52**	**4.36**


Current (A)		
240V	415V	720V
12.5	**7.25**	**4.18**

MECHANICAL DATA


IM B3




IM B5




IM B14




IM B34



IM B35





Frame	Foot Mounting					Shaft							General									
	H	A	B	C	K	D	E	F	G	SS	XX	ZZ	AA	AD	HD	AC	L	LCCL	KK	TBS	TBW	TBH
132M	132.0	216	178	89.0	12X15	Ø 38	80.0	10.0	33.0	M 12	28.0	37.0	252.0	318.0	186.0	Ø 265	475/501	535/561	2-M 25X1.5	38.0	112.0	112.0