DATASHEET

IE4 THREE PHASES MOTOR



GENERAL DATA

Motor Code:	**MS4-90L-8**
Power (kW):	**0.55**
Frame Size:	**90L**
Housing Material:	**Aluminium**
Net Weight (kg):	**17.5**
Insulation Class:	**F**
Protection Degree:	**IP55**
Service Duty:	**S1**
Efficiency Class:	**IE4**
Cooling Method:	**IC411**
Standard:	**IEC 60034**
Bearing Types:	**6205 ZZ**
Noise Level (dB):	**56**
Moment of Inertia (kg*m2):	**0.005498**
Ambient Temp.:	**-15C to +40C**
Altitude:	**1000m above sea level**

ELECTRICAL DATA

Power (kW):			**0.55**
Frequency (Hz):			**50HZ**
Speed (RPM):			**710.0**
Eff% (@400V)	**100%: 77**	**75%: 75.4**	**50%: 70.1**
Power Factor (Cos PHI):			**0.52**
Tst/Tn:			**2.5**
Tmax/Tn:			**2.9**
Tmin/Tn:			**2.2**
Ist/In:			**4**
Moment of Inertia (kg*m2):			**0.005498**


Current (A)		
220V	380V	660V
3.6	**2.09**	**1.2**

Current (A)		
230V	400V	690V
3.45	**1.98**	**1.15**


Current (A)		
240V	415V	720V
3.3	**1.91**	**1.1**

MECHANICAL DATA


IM B3




IM B5




IM B14




IM B34



IM B35





Frame	Foot Mounting					Shaft							General									
	H	A	B	C	K	D	E	F	G	SS	XX	ZZ	AA	AD	HD	AC	L	LCCL	KK	TBS	TBW	TBH
90L	90.0	140	125	56.0	10X13	Ø 24	50.0	8.0	20.0	M 8	19.0	25.0	175.0	229.0	139.0	Ø 183	337/367	386/416	1-M 20X1.5	30.0	105.0	105.0